



Bosch Automotive Service Solutions GmbH | Lürriper Str. 62 | 41065 Mönchengladbach

Subject: **Promax Refrigerant Recovery Units**

Dear Customer,

The Promax Refrigerant Recovery Units, truly universal machines capable of recovering CFC, HCFC, HFC and class A2L refrigerants.

On top of the legendary Promax build quality; it features a proven compressor for the fastest refrigerant recovery and it is possible to safely recover class A2L refrigerants such as R32 and R1234yf when operated by properly trained personnel in accordance with acknowledged safety practices and below Notes are respected.

PLEASE NOTE:

That if used for recovery of Class A2L refrigerants such as R32, HFO1234yf, HFO1234ze or R143a, the unit must ONLY be operated by authorized personnel with proper and specific training in the use and handling of these refrigerants.

The unit is **NOT** for use in hazardous/explosive environments.

It **MUST** be ensured prior to use that the operating environment is **FREE** of hazardous concentrations of gases/vapors/dusts and/or fibers.

The **USE** of an appropriate combustible gas leak detector (e.g. TIF 8900) or measuring device to ensure the safety of the working environment is mandatory before operating the Promax Refrigerant Recovery units.

The **USER must** follow the additional **Promax A2L manual instructions** which are available through your supplier or can be obtained upon request.

If not: do not use this equipment in combination with A2L refrigerants.

Bosch Automotive Service Solutions GmbH declines all responsibilities or claims when Promax units are used improperly or not according all recommended/mentioned guidelines.

Rick Pieper
General Manager

23 March 2016